



Brand: BendPak
Models: XPR-18C
Description: Super-Duty Clearfloor Two-Post Lift

- 18,000 pound lifting capacity
- Single piece columns
- Dual hydraulic "Direct-Drive" cylinders
- Electric/hydraulic power system
- Large, oversize, 3/4" thick, A36 steel base plate
- Single-point safety-lock release
- Oversize 53" tall carriage for superior strength and durability
- Extended height top-beam provides greater overhead clearance
- Full-pivoting arms provide increased range for lifting point access
- Self-lubricating, dura-glide polyethylene bearing system
- Safety locks in each column spaced every 3-inches
- Automatic arm restraints
- Heavy-duty dual equalizer cables with oversize cable sheaves
- Padded overhead safety-shutoff bar
- Durable, rubber lift pads with stackable adapters
- Truck and van adapters standard



MODEL	XPR-18C
Lifting Capacity*	18,000 Lbs. / 8165 Kg.
*Max Capacity / Front Axle	9,000 Lbs. / 4082 Kg.
*Max Capacity / Rear Axle	9,000 Lbs. / 4082 Kg.
A - Height Overall: (*)	170" / 4318 mm.
B - Width Overall (Outside of Base Plate):	155" / 3937 mm.
C - Width (Outside of Columns):	144" / 3658 mm.
D - Floor To Overhead Switch: (*)	165" / 4191 mm.
E - Inside Columns:	120" / 3048 mm.
F - Reach (Front Arm Min.):	39" / 991 mm.
G - Reach (Front Arm Max.):	60" / 1524 mm.
H - Reach (Rear Arm Min.):	39" / 991 mm.
I - Reach (Rear Arm Max.):	60" / 1524 mm.
J - Min. Pad Height:	5" / 127 mm.
K - Rise:	69" / 1753 mm.
L - Max Lift Height (Pad Only):	74" / 1880 mm.
M - Max Lift Height (6" Adapter):	80" / 2032 mm.
N - Drive-Thru Clearance:	106" / 2692 mm.
Motor (**)	220 VAC / 60 Hz. 1Ph.
Time of full Rise:	45 Seconds
Max Load Per Arm:	4,500 Lbs. / 2041 Kg.
* An optional bolt-on top extension for columns raises the overhead bar an additional 24". Must be ordered from factory at time of order.	
** Special Voltages Available Upon Request.	
The design, material and specifications are subject to change without notice.	